



**Class I, Div. 1 & 2, Groups C,D
Class II, Div. 1 & 2, Groups E,F,G
Class III**

Listed - File E10514
 Certified - File LR11716
 File 25215
 APPROVED See files for details or call Killark.

FEATURES-SPECIFICATIONS

KDB/KB

Applications

- When installed in the top of an enclosure, these fittings act as breathers
- Bottom installations permit water to drain from the enclosure continuously
- All drains and breathers are designed for use in 1/2" hubs or 1/2" drilled and tapped conduit openings
- KDB-1 can be used as a drain or breather

Features

- Tapered threads (NPT)

Material/Finish

Stainless Steel - KDB-1

Aluminum - KB1B and KB1D

| DRAINS AND BREATHERS | | |
|----------------------|--------------------|--|
| CATALOG NUMBER | DESCRIPTION | SUITABILITIES |
| KDB-1 ①③ | Drain or Breather | CLASS I Div. 1 & 2, Groups C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III |
| KB1B ② | Breather (Group B) | CLASS I Div. 1 & 2, Groups B, C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III |
| KB1D ② | Drain (Group B) | CLASS I Div. 1 & 2, Groups B, C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III |

① UL Listed and CSA Certified

② UL Listed only

③ FM Approved

KSBF

Applications

- When installed in the top of an enclosure, these fittings act as breathers
- Bottom installations permit water to drain from the enclosure continuously
- KSBF breathers and drains are designed for punched M25 entries in standard location or Ex e sheet metal or non-metallic enclosures

Features

- M25 x 1.5 metric threads
- Includes notched locknut

Material/Finish

- Polyamide
- Green in color



KSBF

**EEx e II
Ex e II**

PTB Ex-95.D.3148U

Call for details

| NON-METALLIC DRAINS AND BREATHERS— EEx e II, IP54 RATED | |
|--|-------------|
| CATALOG NUMBER (INCLUDES LOCKNUT) | THREAD SIZE |
| KSBF-M25 | M25 x 1.5 |

