



## CONCRETE RINGS

### APPLICATION


- Concrete rings are used with poured deck (floor) in high-rise construction.
- These boxes are installed on wooden or steel forms. After the forms are removed, the box is flush with the concrete.

### PRODUCT FEATURES


- Flat sides provide excellent contact for locknuts.
- External ears are used to nail the ring to the wood form.
- Ears on inside of box are for fixtures.
- Waxed fixture ears prevent concrete from interfering with the threads.
- The top-cover is removable for before-pour work.
- Rugged metallic construction.

### COMPLIANCE


- All Hubbell concrete rings are CSA certified, unless otherwise stated, and meet the requirements of the Canadian Electrical Code. File numbers are available upon request.




54521




54531




54541




54551




54561




54561-1/2




54571




54581




54591



54560



CBA



53171-ER

CONCRETE RINGS					
Each concrete ring is supplied with one 54560 cover.					
Catalogue Number	Description	Diameter	Depth	Capacity in <sup>3</sup> (ML)	Knockouts
54521	Ring	4"	1-1/2"	18 (294)	1/2"(4), 3/4"(4)
54531	Ring	4"	2"	24 (393)	1/2"(4), 3/4"(4)
54541	Ring	4"	2-1/2"	30 (491)	1/2"(4), 3/4"(4)
54551	Ring	4"	3"	36 (589)	1/2"(4), 3/4"(4)
54561	Ring	4"	3-1/2"	42 (688)	1/2"(4), 3/4"(4)
54561-1/2	Ring	4"	3-1/2"	42 (688)	1/2"(8)
54571	Ring	4"	4"	48 (786)	1/2"(4), 3/4"(2), 1"(2)
54581	Ring	4"	5"	60(983)	1/2"(4), 3/4"(2), 1"(2)
54591	Ring	4"	6"	72 (1179)	1/2"(4), 3/4"(2), 1"(2)
54560	Cover	4"	-	-	1/2"(5)
CBA *	Adaptor	4"	-	-	-
53171-ER	Extension ring (30.0) - for concrete rings only				

\* CBA Adapter - use for mounting and aligning octagonal extension rings.